

## Twintec Storage...

Your Numatic Scrubber Dryer has been designed and constructed to the highest standard. To enable the machine to provide the best possible service, we recommend you ensure your machine is always left in a clean, dry and tidy condition.



Flip Deck Storage

**A clean machine,  
makes for a cleaner floor.**

Twintec machines should be stored with the dirty water (top) tank empty, the separator should be cleaned and allowed to air dry (Follow the instructions overleaf).

It is also recommended you drain any residual water from the bottom tank, to avoid any residue blocking the pump pipes and filters, during storage.

**To avoid stagnant water and odours, drain and clean your machine.**

### The Tanks...

The superstructure comprises of clean and dirty water heavy duty polyform tanks, designed to provide a truly robust structure and is equipped with a series of advanced, yet practical features.



Heavy Duty Polyform dirty water tank



Heavy Duty Polyform clean water tank



Convenient Flexifill 1m easy fill hose



Large capacity trash basket

# Twintec Care / Storage Instructions...

Compatible with the following machines:

TT 345, TT 350, TT 455, TT 3450, TT 4500, TT 4550, TT 3450C, TT 3450CRS, TT 4045, TT 4055 ET 4045, ET 4055, TTB 345, TTB 455, TTB 3450, TTB 4500, TTB 4550, TTB 4552, TTB 4045, TTB 4055, TLB 345, ET 4045, ET 4055, ETB 4045, ETB 4055



Empty the top (dirty) tank and rinse out with clean water.



Remove the basket filter and rinse with clean water.



Using the handle position lever...



... to tilt the handle towards the rear of the machine.



Unlock the separator.



Remove the separator from the machine.



Check and clean the separator gasket.



Clean the barrel filter (rinse with clean water).



Leave the separator resting on the handle when not in use. This allows the machine to be fully ventilated until dry.



[www.numatic.co.uk](http://www.numatic.co.uk)



[www.numatic.fr](http://www.numatic.fr)



[www.numatic.de](http://www.numatic.de)



[www.numatic.nl](http://www.numatic.nl)



[www.numatic.ch](http://www.numatic.ch)



[www.numatic.co.za](http://www.numatic.co.za)

Numatic International Limited, Chard, Somerset, TA20 2GB Tel: +44 01460 68600 Fax: +44 01460 68458  
Specification subject to change without prior notice. TAP 3 06/2013 (A02)